## White Gloss Inverter Systems

Our EASYfit split air conditioners comprises two elements - an internal and an external unit. The internal unit is fitted to a metal mounting plate on a wall in the room to be cooled, whilst the external unit is situated outside the building. The two are connected using copper pipe. The external unit, or condenser, removes the heat from the room and dissipates it outside, along with any condensation that's built-up in the system, whilst the internal unit provides cooling. Our wall split range now come alexa and google home compatible making hand controllers a thing of the past.



## **SPECIFICATIONS**

Model	KFR-33IW/AG	Warranty 1. Installed by F-Gas registered installer. 2. Systems must be convised by F Gas registered installer.
Power Rating (Ph-V-Hz)	1 / 220-240V / 50Hz	1. Installed by F-Gas registered installer.
Capacity BTU/H (cooling) kW	12000 / 3.5 (4)	2. Systems must be serviced by F-Gas registered installer. 3. Warranty + Services must be registered with Air Conditioning Centre.
Capacity BTU/H (heating) kW	12000 / 3.5 (4.3)	
Power Input (W) Cooling/Heating	1400~1270	
Current Input (A) Cooling/Heating	4.9 ~ 4.5	
SEER (BTU/hr.w)	6.1	
SCOP (W/W)	4.0	FEATURES
Dehumidification (L/h)	1.3	
Indoor Noise Level dB(A) (Hi/M/Lo)	28~40	Compatible with Amazon and Goole home
Outdoor Noise Level dB(A)	63	Adjustable fan speeds for rapid cooling or minimum noise
Indoor Airflow (m3/h) (Hi/M/Lo)	600 max	
Current Rating (A) Fuse Rating (type D)	8	Heat-pump model provides heating as well as cooling
Net Dimension (mm) indoor (W/D/H)	780x276x202	
Dimension (mm) outdoor (W/D/H)	715x235x540	Oscillating air vanes for dissipation of cold air
Net/Gross Weight (kg) indoor	10	A timer facture that will ture the unit on and off outematically
Net/Gross Weight (kg) outdoor	34	A timer feature that will turn the unit on and off automatically
Max Room Size (m²)	16-30	High efficiency air filters to remove odours and particles
Max Conservatory Size (m²)	15	
Pipe Length (m)	4	Anti-mould coating for hygienic operation
Pipe Diameter Liquid/Gas (Inch)	1/4 & 3/8	Digital display to show operational softings and tomporature
Temp Range °C	16-32	Digital display to show operational settings and temperature
Operating Temp (Cooling/Heating)	-15 / -10	All our systems will Heat the
Restart after Power Failure	Yes	All our systems will Heat the
Refrigerant Leak Detection & Self Diagnosis Systems	Yes	room as well when required.

All ACC product's are guaranteed for 12 months (unless otherwise stated) from the date of original purchase.

