REPLACYL

BY



THE STAINLESS STEEL REPLACEMENT FOR COPPER VENTED CYLINDERS

 Ø COMPETITIVELY PRICED

 Ø NEXT DAY DELIVERY

WHAT ARE THE BENEFITS?

The true replacement for the copper equivalent having BS1566 tapping heights

Supplied complete with compression fittings

O-Ring supplied for seating of immersion element

Complete with power shower take-off/secondary return as standard

Please note that full incoloy immersion element including stat is required. These are available at the time of order for £15.

WHAT SIZES ARE AVAILABLE?







GAS OR OIL BOILERS

REPLACYL
BY
G GLEDHILL



HEATER

REPLACYL DIRECT

Code	ErP rating	Cylinder height (inches)	Cylinder diameter (inches)	Cylinder height (mm)	Cylinder diameter (mm)	Capacity (litres)
SEREP36X18DIR	С	36	18	900	450	117

REPLACYL INDIRECT

Code	ErP rating	Cylinder height (inches)	Cylinder diameter (inches)	Cylinder height (mm)	Cylinder diameter (mm)	Capacity (litres)
SEREP36X18IND	С	36	18	900	450	117
SEREP42X18IND	С	42	18	1050	450	140
SEREP48X18IND	С	48	18	1200	450	162
SEREP36X16IND	С	36	16	900	400	96
SEREP42X16IND	С	42	16	1050	400	114